## Microstructure Mechanics

Polymers: Structure and Properties

**Dierk Raabe** 




WWW.MPIE.DE d.raabe@mpie.de

## **Technology Status A380 – Material Distribution (courtesy Airbus)**







#### Technology Status A380 – Material Distribution (courtesy Airbus)






**GLARE:** "Glass Laminate Aluminium Reinforced Epoxy"

several thin layers of metal (usually <u>aluminium</u>) interspersed with layers of <u>glass-fibre</u> "<u>pre-preg</u>", bonded together with a matrix such as <u>epoxy</u>.

Uni-directional pre-preg layers may be aligned in different directions to suit the predicted <u>stress</u> conditions.

Next generation: CFK







- Improved Stiffness
- Improved hot-wet shear
- Material Optimised Hybrid
- Cost reduction
- Design rules
  - Fiber dominated
  - Bonded Metal laminate











## **Polymers: Introduction**


- Polymers materials consisting of polymer molecules that consist of repeated chemical units ('mers') joined together, like beads on a string. Some polymer molecules contain hundreds or thousands of monomers and are often called macromolecules.
- ➤ Polymers may be **natural**, such as leather, rubber, cellulose or DNA, or **synthetic**, such as nylon or polyethylene.

#### **Structure of polymers**



- Macromolecules are formed by linking of repeating units through covalent bonds in the main backbone
- Properties of macromolecules are determined by
  - molecular weight
  - length
  - backbone structure
  - side chains
  - crystallinity
- Resulting macromolecules have huge molecular weights






#### Types of polymers




- Polymer molecules can be very large (macromolecules)
- Most polymers consist of long and flexible chains with a string of C atoms as a backbone
- Side-bonding of C atoms to H atoms or radicals
- Double bonds are possible in both chain and side bonds
- Repeat unit in a polymer chain ("unit cell") is a mer
- Small molecules from which polymer is synthesized is monomer. A single mer is sometimes also called a monomer.

polyethylene (e.g. paraffin wax for candles)









| Structure                 | Source-Based Name         | Application  |  |
|---------------------------|---------------------------|--------------|--|
| R = -H                    | Polyethylene              | Plastic      |  |
| $R = -CH_3$               | Polypropylene             | Rope         |  |
| R = -Cl                   | Poly(vinyl chloride)      | "Vinyl"      |  |
| $X = -H, R = -C_2H_5$     | Poly(ethyl acrylate)      | Latex paints |  |
| $X = -CH_3$ , $R = -CH_3$ | Poly(methyl methacrylate) | Plastic      |  |
| R = -H                    | Polybutadiene             | Tires        |  |
| $R = -CH_3$               | Polyisoprene              | Tires        |  |
| X = -F, R = -F            | Polytetrafluoroethylene   | Teflon®      |  |

#### **Types of polymers**



polytetraflouroethylene PTFE – Teflon

every fourth hydrogen poly(vinyl chloride) PVC


group (CH<sub>3</sub>): polyproplylene PP

#### Polymer structure: large variety in conformation








#### Molecular shape (conformation)



- The angle between the singly bonded carbon atoms is ~109° - carbon atoms form a zigzag pattern in a polymer molecule.
- Moreover, while maintaining the 109° angle between bonds polymer chains can rotate around single C-C bonds (double and triple bonds are very rigid).













1 Linear polymers: Van der Waals bonding between chains. Examples: polyethylene, nylon.








2 Branched polymers: Chain packing efficiency is reduced compared to linear polymers - lower density








3 Cross-linked polymers: Chains are connected by covalent bonds. Often achieved by adding atoms or molecules that form covalent links between chains. Many rubbers have this structure.



#### **Polymer structure**




4 Network polymers: 3D networks made from trifunctional mers. Examples: epoxies, phenol-





#### Polymer structure: overview






Schematic illustration of polymer chains.

- (a) Linear structure; thermoplastics such as acrylics, nylons, polyethylene, and polyvinyl chloride have linear structures.
- (b) Branched structure, such as polyethylene.
- (c) Crosslinked structure; many rubbers and elastomers have this structure. Vulcanization of rubber produces this structure.
- (d) Network structure, which is basically highly cross-linked; examples include thermosetting plastics such as epoxies and phenolics.



Atomic arrangement in polymer crystals more complex than in metals or ceramics (unit cells are typically large and complex).




Polyethylene

#### Polymer structure, crystals and amorphous structure








Polymer molecules are often partially crystalline (semicrystalline), with crystalline regions dispersed within amorphous material.


## Structure, scales, partially crystalline polymers






## Structure, scales, partially crystalline polymers






#### Structure, scales, partially crystalline polymers






The crystalline unit cell for PET (a = 4.56 Å, b = 5.94 Å, c = 10.75 Å;  $\alpha = 98.5^{\circ}$ ,  $\beta = 118^{\circ}$ ,  $\gamma = 112^{\circ}$ ),

M Durell (2002)









PET / AFM: M Durell, J E Macdonald, D Trolley, Europhysics Letters (2002)



Thin crystalline platelets grown from solution - chains fold back and forth: chain-folded model






The average chain length can be much greater than the thickness of the crystallite





**Spherulites:** Aggregates of lamellar crystallites  $\sim 10$  nm thick, separated by amorphous material. Aggregates are formed upon solidification from a melted state and are approximately spherical in shape.















1 micron square, AFM



1 millimeter square, OM





Fig. 2 AFM contact mode images. Cellulose molecules in micro-fibril crystal: (a) topographic image; and (b) error-signal image. Polybutene-1 molecules: (c) topographic image; and (d) simulated AFM image based on crystallographic data.

M. Miles, M. Antognozzi, H. Haschke, J. Hobbs, A. Humphris, I. McMaster H.H. Wills Physics Laboratory, University of Bristol, Materials Today, Feb. 2003








Bamford, Nature 173 (1954) p. 27; Astbury, Endeavor 1(1942) p. 70

#### Polymer structure: PP: XRD





#### Polymer structure: deformation of semi-crystalline polymers




Structure of semicrystalline polymers on a molecular scale can be approximated as consisting of two phases:

- (a) crystalline regions
- (b) disordered quasi-amorphous interlamellar (IL) regions.

Crystal regions typically consist of crystal lamellae by regular folding chains. Within the IL regions four types of molecules are present


- (a)- tails with one free end;
- (b)- loops, which start and end in the same lamellae;
- (c)- bridges (tie molecules) which join up two lamellae
- (d)- floating molecules which are unattached to any lamella



## Polymer structure: deformation of semi-crystalline polymers








#### **Polymers: mechanical properties – trends**






General terminology describing the behavior of three types of plastics. PTFE is polytetrafluoroethylene (Teflon, a trade name). Source: After R.L.E. Brown.

#### Polymers: mechanical properties – the influence of temperature







Behavior of polymers as a function of temperature and (a) degree of crystallinity and (b) crosslinking. The combined elastic and viscous behavior of polymers is known as viscoelasticity.

#### Polymers: mechanical properties – the influence of temperature









Effect of temperature on the stress-strain curve for cellulose acetate, a thermoplastic. Note the large drop in strength and increase in ductility with a relatively small increase in temperature.

Source: After T.S. Carswell and H.K. Nason.

Effect of temperature on the impact strength of various plastics. Note that small changes in temperature can have a significant effect on impact strength.

Source: P.C. Powell.





## **Durability of polymer composites**

# Polymer composites change with time and most significant factors are

- Elevated temperatures
- Fire
- Moisture
- Adverse chemical environments
- Natural weathering when exposed to sun's ultra-violet radiation

#### Polymer composites: mechanical properties





| MATERIAL                        | Relative<br>density | Diameter<br>thickness<br>ratio<br>(microns) | Length<br>(mm) | E<br>(GPa) | Tens.<br>Str.<br>(MPa) | Failure<br>strain<br>(%) | Volume in composite (%) |
|---------------------------------|---------------------|---|----------------|------------|------------------------|--------------------------|-------------------------|
| Mortar matrix                   | 1.8-2.0             | 300-5000                                    | -              | 10-30      | 1-10                   | 0.01-0.05                | 85-97                   |
| Concrete matrix                 | 1.8-2.4             | 10000-20000                                 | -              | 20-40      | 1-4                    | 0.01-0.02                | 97-99.5                 |
| Asbestos                        | 2.55                | 0.02-30                                     | 5-40           | 164        | 200-1800               | 2-3                      | 5-15                    |
| Carbon                          | 1.16-1.95           | 7-18  | 3-cont.        | 30-390     | 600-2700               | 0.5-2.4                  | 3-5                     |
| Glass                           | 2.7                 | 12.5  | 10-50          | 70         | 600-2500               | 3.6                      | 3-7                     |
| Polyethylene                    |                     |   | 1              | 1          |                        |                          |                         |
| HDPE filament                   | 0.96                | 900   | 3-5            | 5          | 200                    | -                        | 2-4                     |
| High modulus                    | 0.96                | 20-50                                       | Cont.          | 10-30      | > 400                  | > 4                      | 5-10                    |
| Polypropylene<br>(Monofilament) | 0.91                | 20-100                                      | 5-20           | 4          | -                      | -                        | 0.1-0.2                 |
| Polyvinyl alcohol<br>(PVA)      | 1-3                 | 3-8   | 2-6            | 12-40      | 700-1500               | -                        | 2-3                     |
| Steel                           | 7.86                | 100-600                                     | 10-60          | 200        | 700-2000               | 3-5                      | 0.3-2.0                 |

#### Performance is controlled by

- vol. fraction of fibers
- properties of fibers and matrix
- bond between the two

## Polymer composites: mechanical properties



|                             |           |            | Elongation<br>in 50 mm | Poisson's<br>ratio |
|-----------------------------|-----------|------------|------------------------|--------------------|
| Material                    | UTS (MPa) | E (GPa)    | (%)                    | $(\nu)$            |
| ABS                         | 28–55     | 1.4-2.8    | 75–5                   |                    |
| ABS (reinforced)            | 100       | 7.5        | _                      | 0.35               |
| Acetals                     | 55-70     | 1.4 - 3.5  | 75 - 25                | _                  |
| Acetals (reinforced)        | 135       | 10         | _                      | 0.35 - 0.40        |
| Acrylics                    | 40 - 75   | 1.4 – 3.5  | 50-5                   | _                  |
| Cellulosics                 | 10 – 48   | 0.4 - 1.4  | 100-5                  | _                  |
| Epoxies                     | 35 - 140  | 3.5 - 17   | 10-1                   | _                  |
| Epoxies (reinforced)        | 70 - 1400 | 21 - 52    | 4-2                    | _                  |
| Fluorocarbons               | 7–48      | 0.7 - 2    | 300-100                | 0.46 – 0.48        |
| Nylon                       | 55–83     | 1.4 - 2.8  | 200-60                 | 0.32 - 0.40        |
| Nylon (reinforced)          | 70 - 210  | 2-10       | 10-1                   | _                  |
| Phenolics                   | 28 - 70   | 2.8 - 21   | 2-0                    | _                  |
| Polycarbonates              | 55-70     | 2.5 - 3    | 125 - 10               | 0.38               |
| Polycarbonates (reinforced) | 110       | 6          | 6-4                    | _                  |
| Polyesters                  | 55        | 2          | 300-5                  | 0.38               |
| Polyesters (reinforced)     | 110 – 160 | 8.3 - 12   | 3-1                    | _                  |
| Polyethylenes               | 7-40      | 0.1 - 0.14 | 1000-15                | 0.46               |
| Polypropylenes              | 20 - 35   | 0.7 - 1.2  | 500 - 10               | _                  |
| Polypropylenes (reinforced) | 40 – 100  | 3.6-6      | 4-2                    | _                  |
| Polystyrenes                | 14 - 83   | 1.4 - 4    | 60-1                   | 0.35               |
| Polyvinyl chloride          | 7-55      | 0.014-4    | 450 – 40               | _                  |

Approximate range of mechanical properties for various engineering plastics at room temperature.

#### Polymer structure: deformation of polymers-based composites





|               | 7D 11          | T31           | ъ          | D 1 44   |
|---------------|----------------|---------------|------------|----------|
|               | Tensile        | Elastic       | Density    | Relative |
| Туре          | Strength (MPa) | Modulus (GPa) | $(kg/m^3)$ | Cost     |
| Boron         | 3500           | 380           | 2600       | Highest  |
| Carbon        |                |               |            |          |
| High strength | 3000           | 275           | 1900       | Low      |
| High modulus  | 2000           | 415           | 1900       | Low      |
| Glass         |                |               |            |          |
| E type        | 3500           | 73            | 2480       | Lowest   |
| S type        | 4600           | 85            | 2540       | Lowest   |
| Kevlar        |                |               |            |          |
| 29            | 2800           | 62            | 1440       | High     |
| 49            | 2800           | 117           | 1440       | High     |
| 129           | 3200           | 85            | 1440       | High     |
| Nextel        |                |               |            | _        |
| 312           | 1630           | 135           | 2700       | High     |
| 610           | 2770           | 328           | 3960       | High     |
| Spectra       |                |               |            | _        |
| 900           | 2270           | 64            | 970        | High     |
| 1000          | 2670           | 90            | 970        | High     |
| 37 ( 77)      |                |               |            |          |

Note: These properties vary significantly, depending on the material and method of preparation. Strain to failure for these fibers is typically in the range of 1.5% to 5.5%.

Typical properties of reinforcing fibers

# Microstructure Mechanics


Biological (Natural) Materials


**Dierk Raabe** 




WWW.MPIE.DE d.raabe@mpie.de








- complex structure
- hierarchical structure
- soft matter plus ceramics

















### **Compact bone: mesoscopic structure**















#### **Bone: details of osteon structure**








#### Bone: details of osteon structure: Overview








#### **Bone: details of osteon structure: Overview**







### Bone: macroscopic mechanical properties: human materials






Very high variety by structure modification, particularly mineral content modification

Self-repair

Stiffness scaling by mineral content

|                        | Ultimate<br>Comp. Str.<br>(MPa) | Modulus of<br>Elasticity<br>(GPa) |
|------------------------|---------------------------------|-----------------------------------|
| <b>Cortical Bone</b>   | 140 - 200                       | 14 - 20                           |
| <b>Cancellous Bone</b> | 5 - 60                          | 0.7 - 1.5                         |
| Synthetic HA           | 200 - 900                       | 34 - 100                          |
| Bone Mineral           | 25 6<br>(anorganic bone)        |                                   |



# chitin: 3 examples



Homarus americanus



Carabus auronitens











## **Introduction - Arthropod cuticle**





Main exoskeleton component of more than 90% of all animal species ...



adaptive material -> candidate for bio-inspired material

### Crustacean cuticle (subgroup of arthropods)





- cuticle surrounds the whole animal
- forms different skeletal elements
- cover a vast variety of physical properties
- adapted to:
  - the specific function of the skeletal element
  - ecophysiological strains of the animal



Birgus latro



Porcellio scaber



Armadillidium vulgare



Horseshoe crab




Homarus americanus

hierarchical structure follows the same principle regardless of the specific properties of the cuticle

## The materials science of the arthropods










#### Structure hierarchy of arthropods







Al-Sawalmih, C. Li, S. Siegel, H. Fabritius, S.B. Yi, D. Raabe, P. Fratzl, O. Paris: Advanced functional materials 18 (2008) 3307 H. Fabritius, C. Sachs, S. Nikolov, and D. Raabe, Advanced materials











100 µm






























200nm Mag = 100.00 K X WD = 3 mm Signal A = InLens EHT = 5.00 kV Date :20 Ja

### Compression tests (macroscopic), lobster











## Mechanical properties (microscopic)






#### nanoindentation







Variations in mechanical properties are the result of structural and chemical variations within the hierarchical level rather than by changes in the overal structural organisation



































multicomponent hygroscopic anisotropic inhomogeneous discontinuous inelastic fibrous porous biodegradable renewable




Eastern white pine in 3-D view, magnified 150x (Source: 1980. Panshin, A.J. and C. de Zeeuw, Textbook of Wood Technology, McGraw Hill, page 128).



## **Wood: Microstructure hierarchy**






#### Wood: Microstructure hierarchy: Bamboo








### **Comparison: Wood and Bone**







## Wood: Composition of cell wall of wood




| Material |   | Structure               | Approx. wt % |
|----------|---|-------------------------|--------------|
| Fibres   | Cellulose (C <sub>6</sub> H <sub>10</sub> O <sub>5</sub> ) <sub>n</sub> | Crystalline             | 45           |
| Matrix   | Lignin  | Amorphous               | 20           |
|          | Hemicellulose   | Semi-crystalline        | 20           |
|          | Water   | Dissolved in the matrix | 10           |
|          | Extractives   | Dissolved in the matrix | 5            |









| Softwood  | Hardwood   |  |
|---|--|--|
| Larger, longer cells Water transported by cells | Contains large-diameter vessels Water transported by these vessels |  |
|   |  |  |








### **Density vs Strength Correlation**






# How does wood compare? (Tensile strength)



#### Wood: mechanical properties: Hardness







#### Wood: mechanical properties: property map: specific strength






Figure 9-14: Structural materials stiffness and strength.